

# TIP FORCE™ 250 Smoothbore Nozzle



## Overview

The HEN® TIP FORCE™ 250 nozzle delivers a smoothbore-like performance with a tight, solid stream, maximizing reach and penetration for effective fire suppression while maintaining the benefits of a pressure-managed nozzle. Flowing 946 LPM at 310 kPa with only 89 lbs of nozzle reaction. The TIP FORCE™ sets the industry standard for low-pressure PSI nozzles.

## Features

- Solid tight pattern with large water droplets
- Hard-coat anodized aluminum construction
- Available with 1.5" NH & 1.5" NPSH threads
- Full-time swivel
- NFPA 1960/1964 compliant
- 5-Year Warranty

## Specifications

	IMPERIAL	METRIC
Target Flow	250 GPM	946 LPM
Target Pressure	45 PSI	310 kPa
Weight	1.1 lb	0.50 kg
Length	6.0 in.	152.4 mm
Width	2.7 in.	69 mm

## Flow Rates

PRESSURE KPA (PSI)	FLOW RATE LPM (GPM)
207 (30)	779 (206)
310 (45)	955 (252)
345 (50)	1,006 (266)
414 (60)	1,102 (291)
483 (70)	1,190 (314)



**NFPA  
COMPLIANT**