

# BLADE™ 185

## Combination Smoothbore Nozzle




### Overview

The HEN® BLADE™ combination smoothbore nozzle redefines fire attack by combining the reach and penetration of a traditional smoothbore with the versatility of an in-line BLADE™ pattern. With a simple quarter-turn, firefighters can transition from a tight, solid stream to a wide, high-impact BLADE™ stream, delivering large water droplets for maximum efficiency, improved cooling, and enhanced control.

### Specifications

	IMPERIAL	METRIC
Target Flow	185 gpm	750 lpm
Target Pressure	50 psi	4 bar
BLADE™ Pattern Angle	22°	22°
Weight	1.7 lb	0.77 kg
Length	6.6 in.	168 mm
Width	3.2 in.	81 mm

### Coverage



### Features

- Quarter-turn from solid linear BLADE™ pattern to solid tight pattern
- Hard-coat anodized aluminum construction
- Available with 1.5" NH and 1.5" NPSH threads
- Full-time swivel
- NFPA 1960/1964 compliant
- 5-Year Warranty

### Flow Rates

PRESSURE KPA (PSI)	FLOW RATE LPM (GPM)
207 (30)	541 (143)
276 (40)	625 (165)
345 (50)	700 (185)
414 (60)	765 (202)
483 (70)	825 (218)



**NFPA  
COMPLIANT**