

# BLADE FORCE™ 250

## Combination Smoothbore Nozzle



### Overview

The HEN® BLADE FORCE™ nozzle combines the power of a smoothbore nozzle with a solid linear BLADE™ stream, delivering both a tight, solid stream for penetration and a blade-like pattern for enhanced fire attack versatility and coverage. Flowing at 250gpm @ 45psi with just 89lbs of nozzle reaction. The BLADE FORCE™ sets the industry standard for low pressure PSI nozzles.

### Features

- Solid tight pattern with large water droplets
- Works with ALL 2", 2.25", & 2.5" hoseline
- 250 GPM @ 45 PSI nozzle pressure
- Hard-coat anodized aluminum construction
- Available with 1.5" NH & 1.5" NPSH threads
- NFPA 1960/1964 compliant
- 5-Year Warranty

### Specifications

	IMPERIAL	METRIC
Target Flow	250 gpm	940 lpm
Target Pressure	45 psi	3 bar
BLADE™ Pattern Angle	22°	22°
Weight	1.9 lb	0.86 kg
Length	7.2 in.	183 mm
Width	3.4 in.	86 mm

### Flow Rates

PRESSURE PSI (BAR)	FLOW RATE GPM (LPM)
30 (2.1)	205 (776)
45 (3.1)	251 (951)
50 (3.4)	265 (1002)
60 (4.1)	290 (1098)
70 (4.8)	313 (1186)



**NFPA  
COMPLIANT**