

HYDRO® 100

Shutoff



Overview

HYDRO® shutoff with 1-inch waterway. High durability shutoff with full-ball valve, designed for superior flow performance while minimizing resistance and enhancing firefighter control. The HYDRO® shutoff provides superior flow with less waterway turbulence.

Features

- Gate-ball design maintains stream quality when baled-down
- Lightweight
- Hard-coat anodized aluminum body and all-metal ball
- Inlet Threads: 1" NH, 1" NPSH, 1.5" NH, and 1.5" NPSH
- Outlet Threads: 1" NH, 1" NPSH, 1.5" NH, and 1.5" NPSH
- Full-time swivel
- NFPA 1964 compliant
- 5 Year Warranty
- Pistol grip available

Specifications

	IMPERIAL	METRIC
Waterway Size	1.00 in.	25 mm
Rated Pressure	200 PSI	1,379 kPa
Weight (1" / 1.5" thread)	1.2 / 1.3 lb	0.5 / 0.6 kg
Length (1" / 1.5" thread)	4.7 / 4.7 in.	119 / 119 mm
Width (1" / 1.5" thread)	3.5 / 3.5 in.	89 / 89 mm
Height (1" / 1.5" thread)	4.1 / 4.4 in.	104 / 112 mm

