

TIP 265

Smoothbore Nozzle

Overview

The TIP 265 is a 2.5" smoothbore nozzle tip engineered for high-rise, commercial, and standpipe operations. The TIP delivers 265 GPM at 50 PSI for maximum efficiency, as the smoothbore design produces a solid, concentrated stream for superior reach and penetration. Designed to pair with the HEN HYDRO® 200 shutoff, the TIP 265 offers reliable performance in demanding fireground conditions.

Specifications

	IMPERIAL	METRIC
Target Flow	265 gpm	1000 lpm
Target Pressure	50 psi	3.5 bar
Weight	1.2 lb	0.54 kg
Length	7 in.	177.8 mm
Width	3.7 in.	94 mm



Features

- Solid tight pattern with large water droplets
- Hard-coat anodized aluminum construction
- Available with 2.5" NH or 2.5" NPSH threads
- Perfect for high-rise, commercial, and standpipe operations
- NFPA 1960/1964 compliant
- 5-Year Warranty

Flow Rates

PRESSURE PSI (BAR)	FLOW RATE GPM (LPM)
30 (2.1)	206 (779)
45 (3.1)	252 (955)
50 (3.4)	266 (1006)
60 (4.1)	291 (1102)
70 (4.8)	314 (1190)



**NFPA
COMPLIANT**