

# BLADE™ 20

## Combination Smoothbore Nozzle



### Overview

The HEN® BLADE™ combination smoothbore nozzle redefines fire attack by combining the reach and penetration of a traditional smoothbore with the versatility of an in-line BLADE™ pattern. With a simple quarter-turn, firefighters can transition from a tight, solid stream to a wide, high-impact BLADE™ stream, delivering large water droplets for maximum efficiency, improved cooling, and enhanced control.

### Specifications

	IMPERIAL	METRIC
Target Flow	20 GPM	75 LPM
Target Pressure	100 PSI	690 kPa
BLADE™ Pattern Angle	22°	22°
Weight	1 lb	0.45 kg
Length	5.0 in.	127 mm
Width	2.5 in.	64 mm

### Coverage

WIDTH	REACH
10'	25'
8'	20'
6'	15'
4'	10'
2'	5'

### Features

- Quarter-turn from solid linear BLADE™ pattern to solid tight pattern
- Hard-coat anodized aluminum construction
- Available with 1" NH and 1" NPSH threads
- Full-time swivel
- NFPA 1960/1964 compliant
- 5-Year Warranty

### Flow Rates

PRESSURE KPA (PSI)	FLOW RATE LPM (GPM)
345 (50)	54 (14)
517 (75)	66 (17)
690 (100)	76 (20)
862 (125)	85 (22)
1,034 (150)	93 (25)

