

# BLADE FORCE™ 250

## Combination Smoothbore Nozzle



### Overview

The HEN® BLADE FORCE™ nozzle combines the power of a smoothbore nozzle with a solid, linear BLADE™ stream, delivering both a tight, solid stream for penetration and a blade-like pattern for enhanced fire-attack versatility and coverage. Flowing 946 LPM at 310 kPa with only 89 lbs of nozzle reaction. The BLADE FORCE™ sets the industry standard for low-pressure PSI nozzles.

### Features

- Solid tight pattern with large water droplets
- Works with ALL 2", 2.25", & 2.5" hoselines
- 946 LPM at 310 kPa nozzle pressure
- Hard-coat anodized aluminum construction
- Available with 1.5" NH & 1.5" NPSH threads
- NFPA 1960/1964 compliant
- 5-Year Warranty

### Specifications

	IMPERIAL	METRIC
Target Flow	250 GPM	940 LPM*
Target Pressure	45 PSI	310 kPa
BLADE™ Pattern Angle	22°	22°
Weight	1.9 lb	0.86 kg
Length	7.2 in.	183 mm
Width	3.4 in.	86 mm

### Flow Rates

PRESSURE KPA (PSI)	FLOW RATE LPM (GPM)
207 (30)	776 (205)
310 (45)	951 (251)
345 (50)	1,002 (265)
414 (60)	1,098 (290)
483 (70)	1,186 (313)



**NFPA  
COMPLIANT**