

HYDRO® 138

Shutoff



Overview

HYDRO® shutoff with 1.38-inch waterway. High durability shutoff with full-ball valve, designed for superior flow performance while minimizing resistance and enhancing firefighter control. The HYDRO® shutoff provides superior flow with less waterway turbulence.

Features

- Full-ball design provides a smoother movement throughout
- Lightweight
- Hard-coat anodized aluminum body and all-metal ball
- Inlet Threads: 1.5" NH, 1.5" NPSH, 2.5" NH, and 2.5" NPSH
- Outlet Threads: 1.5" NH, and 1.5" NPSH
- Full-time swivel
- NFPA 1964 compliant
- 5 Year Warranty
- Pistol grip available

Specifications

	IMPERIAL	METRIC
Waterway Size	1.375 in.	35 mm
Rated Pressure	200 PSI	1,379 kPa
Weight (1.5" / 2.5" thread)	2.65 / 3 lb	1.2 / 1.4 kg
Length (1.5" / 2.5" thread)	5.2 / 5.2 in.	132 / 132 mm
Width (1.5" / 2.5" thread)	4.1 / 4.1 in.	104 / 104 mm
Height (1.5" / 2.5" thread)	5.2 / 5.7 in.	132 / 145 mm



**NFPA
COMPLIANT**