

# BLADE™ 20

## Combination Smoothbore Nozzle



### Overview

The HEN® BLADE™ combination smoothbore nozzle redefines fire attack by combining the reach and penetration of a traditional smoothbore with the versatility of an in-line BLADE™ pattern. With a simple quarter turn, firefighters can transition from a tight solid stream to a wide, high-impact BLADE™ stream, delivering large water droplets for maximum efficiency, improved cooling, and enhanced control.

### Specifications

	IMPERIAL	METRIC
Target Flow	20 gpm	75 lpm
Target Pressure	100 psi	7 bar
BLADE™ Pattern Angle	22°	22°
Weight	1 lb	0.45 kg
Length	5.0 in.	127 mm
Width	2.5 in.	64 mm

### Coverage

WIDTH	REACH
10'	25'
8'	20'
6'	15'
4'	10'
2'	5'

### Features

- Quarter-turn from solid linear BLADE™ pattern to solid tight pattern
- Hard-coat anodized aluminum construction
- Available with 1" NH and 1" NPSH threads
- Full-time swivel
- NFPA 1960/1964 compliant
- 5-Year Warranty

### Flow Rates

PRESSURE PSI (BAR)	FLOW RATE GPM (LPM)
50 (3.4)	14 (54)
75 (5.2)	17 (66)
100 (6.9)	20 (76)
125 (8.6)	22 (85)
150 (10.3)	25 (93)

