

HYDRO FORCE™ 138

Shutoff



Overview

The HYDRO FORCE™ Shutoff is offered in two purpose-built models designed to regulate nozzle pressure and optimize handline performance. The HYDRO FORCE™ 175 is engineered for a 75 PSI inlet pressure, maintaining 25-35 PSI nozzle pressure on 1.5" and 1.75" hose lines while delivering 160-185 GPM with a 60 lb nozzle reaction. The HYDRO FORCE™ 250 supports 2" and 2.5" hose lines, delivering 250 GPM at 10 PSI nozzle pressure with an 89 lb nozzle reaction.

Features

- Full-ball design provides a smoother movement throughout
- Lightweight
- Hard-coat anodized aluminum body and all-metal ball
- Inlet Threads: 1.5" NH, 1.5" NPSH, 2.5" NH, and 2.5" NPSH
- Outlet Threads: 1.5" NH, and 1.5" NPSH
- Full-time swivel
- NFPA 1964 compliant
- 5 Year Warranty
- Pistol grip available

Specifications

	IMPERIAL	METRIC
Waterway Size	1.375 in.	35 mm
Rated Pressure	200 psi	14 bar
Weight (1.5" / 2.5" thread)	2.9 / 3.4 lbs	1.3 / 1.5 kg
Length (1.5" / 2.5" thread)	5.2 / 5.7 in.	132 / 145 mm
Width (1.5" / 2.5" thread)	4.1 / 4.1 in.	104 / 104 mm
Height (1.5" / 2.5" thread)	5.2 / 5.7 in.	132 / 145mm



**NFPA
COMPLIANT**